

Project Location



Environmental Mitigation Measures during operation period

- Monitoring air quality in the parameters of CO, SO₂, NO₂, TSP, THC and PM-10 for ambient air.
- Controlling emission from stack to comply with the emission standard of Ministry of Industry, Thailand.
- Providing preventive maintenance for machines and equipment to keep them in good conditions.
- Controlling the effluent quality to comply with the wastewater standard of Ministry of Industry, Thailand.
- Conducting emergency response exercise regularly.

Project Information

Project Information

The production of ethylene capacity is around 300,000-360,000 ton/year

The production of deep catalytic cracking capacity is around 389,000 ton/year

The production of butane toluene xylene capacity is around 393,600 ton/year

Implementation results of Mitigation and Monitoring Measures

- Ambient air quality: Monitoring CO, SO₂, NO₂, TSP, THC and PM-10 in the ambient air. All parameters comply with standard.
- Air emission from stack: Monitoring CO, SO₂, NO_x, TSP, NH₃ and H₂S emission from stacks. All parameters comply with standard.
- Effluent quality: Monitoring pH, Temperature, COD, TSS, Grease & Oil, NH₃ and H₂S of effluent. All parameters comply with standard.
- Noise pollution : Monitoring Leq24 hr, Leq8 hr, Noise Dose. The monitoring result complies with standard.
- Safety: Conducting emergency response exercise and providing preventive maintenance for emergency alarm system regularly.